

## Salem White Cabinet Specifications

- ① Face Frames  
Face Frames are  $\frac{3}{4}$ " \*  $1\frac{1}{2}$ " solid hardwood. Frames are mortise and tenons construction reinforced with glue and nails. Frames are dadoed to received cabinet ends, top, and bottoms.
- ② Tops & Bottoms  
Tops and bottom panels are  $\frac{1}{2}$ " thick multi-ply hardwood plywood. Tops and bottoms are dadoed into the face frame and end panels. Base bottom panels are  $\frac{3}{8}$ " thick.
- ③ Toe Kicks  
Toe kicks shall be  $\frac{1}{2}$ " thick hardwood plywood.
- ④ End Panels  
End panels are  $\frac{1}{2}$ " thick multi-ply hardwood plywood. All end panels are dadoed into the face frame and recessed  $\frac{3}{16}$ ".
- ⑤ Adjustable Shelves  
Adjustable shelves are  $\frac{5}{8}$ " thick multi-ply hardwood Plywood. Edge banded with wood tapes. (Exceeds industry standards.)
- ⑥ Back Panels  
Back are  $\frac{1}{2}$ " thick multi-ply hardwood plywood. Backs are routed, glued and nailed in cabinet. (Exceeds industry standards.)
- ⑦ Shelf Clips  
Shelf clips are 6mm bore with a fluted Metal clips. Shelves are adjustable on  $2\frac{1}{2}$ " increments.
- ⑧ Doors  
 $\frac{3}{4}$ " HDF door styles with flat panels.
- ⑨ Hinges  
Full Overlay, Concealed, 110 degree opening, with soft closing dampers.
- ⑩ Drawer Boxes  
 $\frac{5}{8}$ " solid hardwood front, back and 2 sides with  $\frac{3}{8}$ " plywood drawer bottoms, Dovetail construction. (Exceeds industry standards.)
- ⑪ Drawer Glides  
Soft Closing Undermount Full Extension Glides ..(Exceeds industry standards)
- ⑫ Base Corner Brackets  
High impact, injection molded plastic.
- ⑬ Hanging Strips  
Hanging strip are  $\frac{3}{4}$ " \*  $1\frac{1}{4}$ " hardwood.

