

Newport Espresso Cabinet Specifications

- ① Face Frames
Face Frames are $\frac{3}{4}$ " * $1\frac{1}{2}$ " solid hardwood. Frames are mortise and tenons construction reinforced with glue and nails. Frames are dadoed to received cabinet ends, top, and bottoms.
- ② Tops & Bottoms
Tops and bottom panels are $\frac{1}{2}$ " thick multi-ply birch hardwood plywood. Tops and bottoms are dadoed into the face frame and end panels. Base bottom panels are $\frac{3}{8}$ " thick.
- ③ Toe Kicks
Toe kicks shall be $\frac{1}{2}$ " thick hardwood plywood.
- ④ End Panels
End panels are $\frac{1}{2}$ " thick multi-ply hardwood plywood. All end panels are dadoed into the face frame and recessed $\frac{3}{16}$ ".
- ⑤ Adjustable Shelves
 $\frac{5}{8}$ " thick multi-ply hardwood Plywood. Edge banded with wood tape.
(Exceeds industry standards.)
- ⑥ Back Panels
Back are $\frac{1}{2}$ " thick multi-birch hardwood plywood. Backs are routed, glued and nailed in cabinet.
(Exceeds industry standards.)
- ⑦ Shelf Clips
6mm bore with a fluted metal clips. Shelves are adjustable on $2\frac{1}{2}$ " increments.
- ⑧ Doors
 $\frac{3}{4}$ " Solid hard Wood door stiles with flat central panel, Shaker style.
(Exceeds industry standards.)

- ⑨ Hinges
Full Overlay, Concealed, 110 degree opening, with soft closing dampers.

- ⑩ Drawer Boxes
 $\frac{5}{8}$ " solid hardwood front, back and 2 sides with $\frac{3}{8}$ " plywood drawer bottoms, Dovetail construction.
(Exceeds industry standards)

- ⑪ Drawer Glides
Soft Closing Undermount Full Extension Glides.
(Exceeds industry standards)

- ⑫ Base Corner Brackets
Base corner brackets are high impact, injection molded plastic.

- ⑬ Hanging Strips
Hanging strip are $\frac{3}{4}$ " * $1\frac{1}{4}$ " hardwood.

